

1. (Amended) A transporting accessory for a vehicle, the transporting accessory comprising:

a base frame mountable to the vehicle, the base frame having two support members;

a second frame having two extension members, each extension member slidably borne by a respective one of the support members, each extension member having at least one guide device and being movable along a path of travel between a first, retracted position and a second, extended position;

a carriage pivotally mounted to the second frame, the carriage having at least one arm, the at least one arm having at least one guide device, the carriage movable between a first, substantially parallel position and a second, inclined position; and

a transport support having at least one track, the at least one track slidably borne by the at least one guide device of the carriage, the transport support being movable along a path of travel between a first, retracted position and a second, extended position and positioned such that the transport support contacts at least one guide device of each extension member when the transport support is in the retracted position.

4. (Amended) The transporting accessory as claimed in claim 3, wherein the actuating mechanism is an electric actuator.

5. (Canceled)

7. (Amended) The transporting accessory as claimed in claim 6, wherein the actuating mechanism is an electric actuator.

Page 100
~~11~~ (New) The transporting accessory as claimed in claim 1, wherein the base frame includes at least one tube member, the at least one tube member being telescopically borne by the base frame, such that the at least one tube member telescopes from the base frame to adjust a width of the base frame.

~~12~~ (New) The transporting accessory as claimed in claim 1, further comprising a drive assembly operable to move the extension members between the first, retracted position and the second, extended position and to move the transport support between the first, retracted position and the second, extended position.

10001520-020402
~~13~~ (New) The transporting accessory as claimed in claim 12, wherein the drive assembly includes a winch, the winch including a drum that is operable to rotate in both clockwise and counter clockwise directions to wind a cable thereon, the cable having a first end mounted to the drum and a second end mounted to the transport support.

~~14~~ (New) The transporting accessory as claimed in claim 1, wherein the transport support includes at least one roller pivotally mounted to the transport support, the at least one roller positioned such that it contacts a ground surface when the transport support is in the extended position.

~~15~~ (New) The transporting accessory as claimed in claim 1, wherein the second frame is swivelly mounted to the base frame.

Rule 1.26

~~22~~¹⁵ (New) The transporting accessory as claimed in claim 6, wherein the drive assembly includes a motor operable to rotate a drive shaft in both clockwise and counter clockwise directions, the drive shaft being axially interconnected to at least one drive gear that rotates clockwise and counter clockwise with the drive shaft, at least one drive chain being interconnected to the at least one drive gear, the at least one drive chain rotates clockwise and counter clockwise with the at least one drive gear.

~~23~~¹⁶ (New) The transporting accessory as claimed in claim ~~22~~¹⁶, wherein the second frame is interconnected to the at least one drive chain.

~~24~~¹⁷ (New) The transporting accessory as claimed in claim 8, wherein the base frame includes at least one side beam, the side beam having at least one aperture therein for mounting the base frame to the vehicle by inserting fasteners into the at least one aperture.

~~25~~¹⁸ (New) The transporting accessory as claimed in claim 8, wherein the carriage is movable between a first, substantially parallel position and a second, inclined position.

~~26~~¹⁹ (New) The transporting accessory as claimed in claim 8, wherein the transport support is positioned such that the transport support contacts at least one roller of each side arm when the transport support is in the retracted position.

~~27~~²⁰ (New) The transporting accessory as claimed in claim 8, wherein the drive assembly includes a winch, the winch includes a drum that is operable to rotate in both clockwise and counterclockwise directions to wind a cable thereon, the cable having a first end mounted to the drum and a second end mounted to the transport support.

SCANNED, #14
94

28

(New) The transporting accessory as claimed in claim 8, wherein the transport support includes at least one roller pivotally mounted to the transport support, the at least one roller positioned such that it contacts a ground surface when the transport support is in the extended position.